



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 10/04/2022 Reviewed on 10/04/2022

### 1 Identification

- · Product Identifier
- · Trade Name: TECHNIPLAST 3D-SC
- · Relevant identified uses of the substance or mixture and uses advised against:
- · Product Description: Raw material for industrial and consumer uses
- · Details of the Supplier of the Safety Data Sheet:
- Manufacturer/Supplier:

Techniart US LLC

201 Montgomery Street, 2nd Floor

Jersey City, NJ 07302 office@techniart-us.com P: +1 (212) 287 9637

· Emergency telephone number: 1-800-633-8253 / Local +1-801-629-0667

## 2 Hazard(s) Identification

· Classification of the substance or mixture:



Skin Corrosion 1C H314 Causes severe skin burns and eye damage.



Acute Toxicity - Oral 4 H302 Harmful if swallowed.

Acute Toxicity - Dermal 4 H312 Harmful in contact with skin.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- · Label elements:
- · Hazard pictograms:





- · Signal word: Danger
- · Hazard-determining components of labeling:

3-aminomethyl-3,5,5-trimethylcyclohexylamine

bis[4-(2,3-epoxypropoxy)phenyl]propane

Hazard statements:

H302+H312 Harmful if swallowed or in contact with skin. H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

· Precautionary statements:

P260 Do not breathe dusts or mists.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing must not be allowed out of the workplace.

(Contd. on page 2)





OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 10/04/2022 Reviewed on 10/04/2022

#### Trade Name: TECHNIPLAST 3D-SC

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312 If swallowed: Call a poison center/doctor if you feel unwell. P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P302+P352 If on skin: Wash with plenty of water.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

P362+P364 Take off contaminated clothing and wash it before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

### · Unknown acute toxicity:

This value refers to knowledge of known, established toxicological or ecotoxicological values. 30 % of the mixture consists of component(s) of unknown toxicity.

- · Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 0 Reactivity = 0

### · HMIS-ratings (scale 0 - 4)



Health = 3 Fire = 0

REACTIVITY 0 Physical Hazard = 0

· Hazard(s) not otherwise classified (HNOC): None known

# 3 Composition/Information on Ingredients

# Non-hazardous components:

25513-64-8 3,3,5-trimethylhexamethylene-diamine

5-25%

- · Chemical characterization: Substance
- · Description: Mixture of substances listed below with non-hazardous additions.

· Dangerous	Dangerous Components:		
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	20-60%	
	Skin Corrosion 1B, H314; Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Sensitization - Skin 1, H317		
	bis[4-(2,3-epoxypropoxy)phenyl]propane ♦ Skin Irritation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1, H317 Specific concentration limits: Eye Irritation 2; H319: C ≥ 5 %	5-20%	
	Skin Irritation 2; H315: C ≥ 5 %		

(Contd. on page 3)





OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 10/04/2022 Reviewed on 10/04/2022

Trade Name: TECHNIPLAST 3D-SC

#### · Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

#### 4 First-Aid Measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Remove the victim to fresh air. Keep warm and calm. Consult a doctor.
- · After skin contact:

Take off contaminated clothes immediately. Wash contaminated skin with a large amount of water and soap. Put on sterile dressing. Contact a doctor immediately.

### · After eye contact:

Contact an ophthalmologist immediately. Protect non-irritated eye, remove contact lenses. Rinse contaminated eyes with water for at 10-15 minutes. Avoid strong stream of water – risk of damage of the cornea.

### · After swallowing:

Do not induce vomiting. Rinse mouth with water. Do not drink alcohol! Never give anything by mouth to an unconscious person. Contact a doctor immediately, show container or label.

- · Information for doctor
- · Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed: Treat symptomatically.

## 5 Fire-Fighting Measures

- Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · For safety reasons unsuitable extinguishing agents: No further relevant information.
- Special hazards arising from the substance or mixture:

During combustion carbon oxides [CO and CO2], nitrogen oxides and ammonia may be produced. Do not inhale combustion products, it may cause health risk.

- Advice for firefighters
- · Special protective equipment for firefighters:

Personal protection typical in case of fire. Do not stay in the fire zone without self-contained breathing apparatus and protective clothing resistant to chemicals. Do not let extinguishing water to reach sewage, surface and ground waters. Cool containers endangered with fire with water fog from a safe distance.

### 6 Accidental Release Measures

### · Personal precautions, protective equipment and emergency procedures:

Limit the access for the outsiders into the breakdown area, until the suitable cleaning operations are completed. Ensure that the effects of breakdown are removed only by properly trained personnel. In case of large spills, isolate the exposed area. Wear personal protective equipment. Avoid contact with skin and eyes. Ensure adequate ventilation. Do not inhale vapours.

### · Environmental precautions:

If larger quantities of the product are released, steps must be taken to prevent its spreading in the environment. Notify relevant emergency services.

#### Methods and material for containment and cleaning up:

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent.

Dispose of contaminated material as waste according to section 13.

Ensure adequate ventilation.

(Contd. on page 4)





OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 10/04/2022 Reviewed on 10/04/2022

Trade Name: TECHNIPLAST 3D-SC

Dispose of the collected material according to regulations.

· Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· PAC-1:	
1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane	39 mg/m³
· PAC-2:	
1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane	430 mg/m <sup>3</sup>
PAC-3:	
1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane	2,600 mg/m <sup>3</sup>

### 7 Handling and Storage

- · Handling
- · Precautions for safe handling:

Handle in accordance with good occupational hygiene and safety practices. Avoid eyes and skin contamination. Do not let product to enter mouth. Avoid vapours inhalation. Ensure adequate local and/or general ventilation. Wear personal protective equipment.

- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities

Store in properly labelled, tightly sealed containers in a dry, cool and well ventilated place. Keep away from food, foodstuffs, animal feed. Recommended storage temperature: 15-30 C. Protect from water and moisture. Avoid fire. Protect from direct sunlight. Opened container should be resealed and kept upright to prevent leaking. Do not store in non-labelled containers.

- · Storage
- · Requirements to be met by storerooms and receptacles: None additional.
- · Information about storage in one common storage facility: Store away from flammable substances.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s): No further relevant information available.

### 8 Exposure Controls/Personal Protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters:
- · Components with occupational exposure limits:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- · Exposure controls:
- Personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment: Not required.

(Contd. on page 5)





OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 10/04/2022 Reviewed on 10/04/2022

Trade Name: TECHNIPLAST 3D-SC

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material:

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· Eye protection:



Tightly sealed goggles

- · Body protection: Not required.
- Limitation and supervision of exposure into the environment: None

## 9 Physical and Chemical Properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid Color: Colorless

· Odor: Characteristic, slightly amine

Odor threshold: Not determined.pH-value: Not determined.

Change in condition

**Melting point/Melting range:** Not determined.

· Flash point: None

Flammability (solid, gaseous): Not applicable.
 Ignition temperature: Not applicable
 Decomposition temperature: Not determined.

· **Auto igniting:** Product is not self-igniting.

• Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower:Not determined.Upper:Not determined.Vapor pressure:Not determined.

(Contd. on page 6)





OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 10/04/2022 Reviewed on 10/04/2022

Trade Name: TECHNIPLAST 3D-SC

• **Density @ 20 °C (68 °F):** 1.05 g/cm³ (8.7623 lbs/gal)

Relative density: Not determined.
 Vapor density: Not determined.
 Evaporation rate: Not determined.

· Solubility in / Miscibility with:

Water: Insoluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

**Dynamic:** Not determined. **Kinematic @ 20 °C (68 °F):** 0.4-0.6 mPas

· Solvent content:

Solids content: 0.0 %

• Other information: No further relevant information available.

### 10 Stability and Reactivity

- · Reactivity: Product is reactive. Undergoes dangerous polymerization.
- · Chemical stability: Product is stable under normal conditions.
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions:

The product may polymerize exothermically in reaction with some substances.

- · Conditions to avoid: Avoid sources of heat and direct sungliht. Protect from moisture.
- · Incompatible materials: Avoid contact with strong oxidizers, acids, bases, amines, water.
- · Hazardous decomposition products:

There are no hazardous decomposition products when product is properly used and stored.

## 11 Toxicological Information

- · Information on toxicological effects:
- · Acute toxicity:
- LD/LC50 values that are relevant for classification: No data available.
- · Primary irritant effect:
- · On the skin:

Corrosive effect on skin and mucous membranes.

Corrosive to skin and mucous membranes.

May cause an allergic skin reaction.

- · On the eye: Corrosive effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Irritant

Swallowing will lead to a corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.

(Contd. on page 7)





OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 10/04/2022 Reviewed on 10/04/2022

Trade Name: TECHNIPLAST 3D-SC

· Carcinogenic categories:

· IARC (International Agency for Research on Cancer):	
1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane	3
· NTP (National Toxicology Program):	
None of the ingredients are listed.	
· OSHA-Ca (Occupational Safety & Health Administration):	
None of the ingredients are listed.	

## 12 Ecological Information

- · Toxicity:
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability: No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential: No further relevant information available.
- Mobility in soil: No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment:
- · **PBT**: Not applicable.
- vPvB: Not applicable.
- · Other adverse effects: No further relevant information available.

#### 13 Disposal Considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household waste. Do not allow product to reach sewage system. Observe all federal, state and local environmental regulations when disposing of this material.

- Uncleaned packaging
- · Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

### 14 Transport Information

· UN-Number:

· **DOT, ADR/ADN, IMDG, IATA** UN2735

· UN proper shipping name:

Amines, liquid, corrosive, n.o.s. (Polyoxypropylene triamine)
ADR/ADN
UN2735 AMINES, LIQUID, CORROSIVE, N.O.S.

(Polyoxypropylene triamine)

· IMDG, IATA AMINES, LIQUID, CORRÓSIVE, N.O.S. (Polyoxypropylene

triamine)

(Contd. on page 8)





OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 10/04/2022 Reviewed on 10/04/2022

Trade Name: TECHNIPLAST 3D-S	С
------------------------------	---

- · Transport hazard class(es):
- · DOT



· Class: 8 Corrosive substances

· Label:

· ADR/ADN



· Class: 8 (C7) Corrosive substances

· Label:

· IMDG, IATA



· Class: 8 Corrosive substances

· Label: 8

· Packing group:

· DOT, ADR/ADN, IMDG, IATA

· Environmental hazards: Not applicable.

· Special precautions for user: Warning: Corrosive substances

· Hazard identification number (Kemler code): 80

· EMS Number: F-A,S-B

Segregation groups: (SGG18) Alkalis

Stowage Category

SG35 Stow "separated from" SGG1-acids · Segregation Code

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code: Not applicable.

· Transport/Additional information:

· DOT

On passenger aircraft/rail: 5 L · Quantity limitations:

On cargo aircraft only: 60 L

· ADR/ADN

Excepted quantities (EQ): Code: E1

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· IMDG

Limited quantities (LQ): 5L

(Contd. on page 9)





OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 10/04/2022 Reviewed on 10/04/2022

Trade Name: TECHNIPLAST 3D-SC

· Excepted quantities (EQ): Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S.

(POLYOXYPROPYLENE TRIAMINE), 8, III

## 15 Regulatory Information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture: No further relevant information available.
- · SARA (Superfund Amendments and Reauthorization):
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients are listed.

- California Proposition 65:
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

New Jersey Right-to-Know List:

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

New Jersey Special Hazardous Substance List:

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

CO

· Pennsylvania Right-to-Know List:

None of the ingredients are listed.

· Pennsylvania Special Hazardous Substance List:

None of the ingredients are listed.

- · Carcinogenic categories:
- · EPA (Environmental Protection Agency):

None of the ingredients are listed.

• TLV (Threshold Limit Value established by ACGIH):

None of the ingredients are listed.

(Contd. on page 10)





OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 10/04/2022 Reviewed on 10/04/2022

Trade Name: TECHNIPLAST 3D-SC

#### · NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

#### · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:





· Signal word: Danger

### · Hazard-determining components of labeling:

3-aminomethyl-3,5,5-trimethylcyclohexylamine bis[4-(2,3-epoxypropoxy)phenyl]propane

#### · Hazard statements:

H302+H312 Harmful if swallowed or in contact with skin. H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

### Precautionary statements:

P260 Do not breathe dusts or mists.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312 If swallowed: Call a poison center/doctor if you feel unwell. P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P302+P352 If on skin: Wash with plenty of water.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

P362+P364 Take off contaminated clothing and wash it before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · National regulations:

The product is not subject to be labelled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of

(Contd. on page 11)





OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 10/04/2022 Reviewed on 10/04/2022

#### Trade Name: TECHNIPLAST 3D-SC

this information and the suitability of the material or product for any particular purpose.

#### · Contact:

#### · Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Toxicity - Oral 4: Acute toxicity - Category 4

Skin Corrosion 1B: Skin corrosion/irritation - Category 1B

Skin Corrosion 1C: Skin corrosion/irritation - Category 1C

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1: Skin sensitisation - Category 1

#### \* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106